

**Instruction Manual for Bayonet Converter  
for NA-TG5 / Olympus PT-058/059**

PN#83255, #83256

**FOREWORD**

Thank you for your purchase of a NAUTICAM product.

At NAUTICAM, we pride ourselves in the ability to recognize the requirements of professional as well as amateur underwater photographers and fulfill them through the innovative designs of our products. We strive to achieve a high level of user-friendliness by allowing stress-free installation and easy operation of all important functions of the camera.

Please read this manual carefully before using the product, this will maximize its performance as well as its lifetime.

**WARRANTY**

All NAUTICAM Products are warranted against any material and manufacturing defects for two years from the date of purchase for consumer use. This warranty only applies to products purchased from authorized NAUTICAM dealers and does not extend beyond the original retail purchaser.

To return your product for service, please contact your regional authorized service center(s). Please note that this warranty only applies when the product is purchased in the territory where the service center is located.

NAUTICAM does not hold responsibility for damage, of any nature, to any equipment used with and/or placed within our products.

NAUTICAM accepts no liability for any loss of captured images or the inability to capture images even if it is due to the malfunctioning of our products.

Unauthorized modifications and/or repairs of our products will automatically invalidate the warranty.

**IDENTIFICATION OF PARTS**



**Bayonet Converter for NA-TG5**



**Bayonet Converter for Olympus PT-058/059**

**INSTALL TO NA-TG5 HOUSING**



Remove the optical fiber connector from housing, then install the optical fiber connector provided.



Align the 4x positioning blocks on the bayonet converter with the slots on the front of the housing.

--- continue on next page ---

--- continued from front page ---



Place the locking ring on the bayonet converter, then fasten the converter on the front of the housing with the fastening tool provided.



Place the locking ring on the bayonet converter, then fasten the converter on the front of the housing with the fastening tool provided.

#### INSTALL TO OLYMPUS PT-058/059



Remove the Olympus optical fiber connector from housing, then install the optical fiber connector provided.



*\*Attention: Before installing WWL-C into the housing, pre-install the optical fiber cables as shown in case of using strobes.*



Align the positioning block on the bayonet converter with the slots on the front of the housing.



Example: WWL-C with bayonet Converter on the NA-TG5 housing.

--- continue on next page ---

--- continued from front page ---

## SPECIFICATIONS

PN#	Description	Weight
83255	Bayonet Converter for NA-TG5 (to use with WWL-1/WWL-C)	125.5g
83256	Bayonet Converter for Olympus PT-058/059 (to use with WWL-1/WWL-C)	124g

## COMPATIBILITY

Compatible Lenses:	83203 Wet Wide Lens Compact (WWL-C) 83214 Bayonet Mount Adaptor for SMC/CMC
--------------------	--

Remark: Nauticam supports only e-manuals. Please download corresponding product manuals on Nauticam.com website, or contact us for e-manuals.

*Current as of 2020-01-03*